



Weighing Technology

# AFW

Intelligent-Weigh™



132lb x0.02lb

330lb x0.05lb

660lb x0.1lb

- Stainless Steel Pan And Pillar
- Animal Weighing Filter
- Keyboard Enabled For lb / kg
- Rechargeable Battery
- Optional Dry Cell Battery Pack
- Optional Wheel Kit



Made in Democratic Taiwan



Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance

AFW Series

Model	AFW-F132	AFW-F330	AFW-F660
Capacity	132 lb / 60 kg	330 lb / 150 kg	660 lb / 300 kg
Readability	0.02 lb / 0.01 kg	0.05 lb / 0.02 kg	0.1 lb / 0.05 kg
Divisions	6,000	7,500	6,000
Weighing Units / Functions	lb / kg, animal weighing		
Stabilization Time	< 2 seconds		
Tare Range	To capacity by subtraction		
Power Source	Built-in rechargeable battery or external power adapter (included)		
Construction	Stainless steel pillar and platform with heavy duty cast aluminum base and rounded safety corners		
Display	1 inch high, 7 segment, wide viewing angle backlit LCD display		
Platform Size (W x D x H)	16.7 x 20.6 x 4.5 inches / 425 x 524 x 115 mm		
Overall Dimensions (W x D x H)	16.7 x 29 x 35 inches / 425 x 737 x 889 mm		
Operating Environment	32 ° F to 104 ° F non condensing R.H. ≤ 95%		
Connectivity	RS232 Interface		
Net Weight	39 lb / 17.7 kg		
Shipping Weight	47 lb / 21.3 kg		
Options	Dry Cell Battery Pack, Wheel Kit		

Features	Benefits
Deep skirted stainless steel platter	Easy to clean for food processing or harsh environments
Overload and shock protection	Will withstand harsh industrial environments
Backlit LCD display with wide viewing angle	Easy to see weight values from a distance, reduces mistakes
Reads in kilograms or pounds	Flexibility of operation
Built-in rechargeable battery and external A/C adapter	Portability, minimum 150 hours
Zero tracking	Ensures that you always start weighing from zero
Automatic power save	Conserves battery power
Low battery indicator & charge status light	Alerts you to charge the battery, saving downtime
Adjustable feet & spirit level	Ensures scale can be leveled on uneven working surfaces
In use dust cover for indicator	Keeps indicator clear from contamination
Indicator rotates through 135 degrees	Enables viewing from all angles
Wide angle LCD display	Can be seen from a wide viewing range in sunshine, ideal for outdoor use
Options for display: platform, pillar or wall mounted (3 ft of cable supplied)	Flexibility of operation and position
Optional auto tare function	Allows the first article on the platter to be automatically tared.
Gravitational correction software	Enables you to input different G acceleration factors



Optional Drycell Battery Pack