



Weighing Technology

TitanN™

Intelligent-Weigh™



50lb x0.01lb
100lb x0.02lb
200lb x0.05lb
500lb x0.1lb



- NTEP Approved Class III
- Cast Aluminum Base & Stainless Platter
- Bi-Directional RS232 Interface
- Large 2" Backlit LCD Display
- Base Only Pricing
- Rechargeable Battery





Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance



TitanN™
Series

Model	TitanN B 50	TitanN B 100	TitanN B 200	TitanN F 100	TitanN F 200	TitanN F 500
Capacity	50 lb / 25 kg	100 lb / 50 kg	200 lb / 100 kg	100 lb / 50 kg	200 lb / 100 kg	500 lb / 250 kg
Readability	0.01 lb / 0.005 kg	0.02 lb / 0.01 kg	0.05 lb / 0.02 kg	0.02 lb / 0.01 kg	0.05 lb / 0.02 kg	0.1 lb / 0.05 kg
Platform Size	14 x 18 x 3.5" 330 x 450 x 95 mm	14 x 18 x 3.5" 330 x 450 x 95 mm	14 x 18 x 3.5" 330 x 450 x 95 mm	16.5 x 20.5 x 4.7" 420 x 520 x 120 mm	16.5 x 20.5 x 4.7" 420 x 520 x 120 mm	16.5 x 20.5 x 4.7" 420 x 520 x 120 mm
Division	5000					
Weighing Units	lb, kg, oz					
Stabilization Time	<3					
Functions	Accumulation					
Tare Range	To capacity by subtraction					
Power Source	Built-in rechargeable battery or external power adapter (included)					
Construction	Stainless steel platform with cast aluminum base					
Display	2" High backlit LCD Display					
Dimensions (L x W x H)	14 x 18 x 3.5"			16 x 20 x 4.5"		
Operating Environment	32°-104° Non condensing R.H. ≤ 95%					
Connectivity	Bi-Directional RS232					
Net Weight	25 lb / 13 kg			36 lb / 17 kg		
Shipping Weight	35 lb / 16 kg			46 lb / 21 kg		
Options	Printer, Dry Cell Battery Pack, Wheel Kit					
Approvals	NTEP Approval CoC #12-077A1 (Base) CoC #17-145 (Indicator)					

Features	Benefits
Overload and shock protection mechanism	Protects against excessive loads and shock applied to platform
Heavy duty rugged construction	Will withstand harsh industrial operation
Low profile, compact size	Space saving, easy to load and unload
Large backlit LCD display with wide viewing angle	Easy to see weight values from a distance, reduces mistakes
Display reads in lb, oz and kg	Flexibility of operation.
Built-in rechargeable battery or external power adapter	Portability. Battery operation minimum 150 hours.
Accumulation function	Allows you to add together consecutive weights to arrive at total
Zero tracking	Ensures that you always start weighing at zero
Automatic power save	Conserves battery power
Low battery indicator / charge status indicator	Alerts you to charge the battery, saving downtime
Easy calibration function	Ensures accuracy
Adjustable feet and spirit level	Scale remains level for accurate results on uneven working surfaces - Anti-slip
Digital motion filtering	Can compensate for harsh environmental conditions
Operational automatic tare	Enables you to disregard the first item places on the platform