



PMI® 1" Fall Protection RB Anchor Hardware | Anchorage Connectors



This anchor can be removed and reused at any desired location. It features unmatched safety, ease of use, and speed. The RB Anchor works in horizontal, vertical, and overhead/ceiling surfaces. Costly engineering inserts are not required. This anchor can be used for fall protection, restraint, work positioning, and more. This product is designed for use in concrete or rock only.

Key Features

- Spring is zinc plated steel
- Swage is zinc plated copper
- Trigger is aluminum alloy
- End termination, spoons, and stop sleeves are stainless steel
- Main cable is 7 x 19 galvanized cable

Additional Information

Shipping weight | 1.2 lbs

MBS | 12 kN (2700 lbf)

Working Load Limit | 2.2 kN (500 lbf)

Height | 1.25" (3.2 cm)

Length | 9.0" (22.9 cm)

Width | 3.65" (9.3 cm)

Weight | 3.2 oz (91 g)

Compliant | ANSI Z359.1 (2007), EN 795

Tags

[fall protection](#), [made in USA](#), [Swage is zinc plated copper](#), [Aluminum alloy trigger](#), [Spring is zinc plated steel](#), [Removable anchor for concrete](#), [Rope Rescue](#), [Rope Access](#), [Wilderness Rescue](#), [Cave Rescue](#), [ANSI Z359.1 Compliant](#), [MBS: 44 kN \(10000 lbf\)](#), [EN 795 Compliant](#)

Product Code

HD26224

