



13 mm PMI® Isostatic Polyester Rope Rope | Static Rope



A PMI signature rope constructed of 100% polyester core and sheath. These ropes are specifically designed with super low elongation for specialty applications such as highlines and applications where professional rope technicians require absolute minimal elongation. These ropes are also engineered to stay rounder and have less sheath slippage than conventional kernmantle polyester ropes.

Key Features

- NFPA Certified
 - 32 carrier construction
 - 100% polyester construction
 - Resists flattening under load
-

Additional Information

Shipping weight | N/A

Color | Blue/White/Green, Orange/White/Green

Length | 30 m (100 ft), 46 m (150 ft), 61 m (200 ft), 92 m (300 ft), 183 m (600 ft), 200 m (656 ft)

Weight | 96 g/m

MBS | 32.8 kN (7388 lbf)

Elongation at 300 lbf | 1.0%

Elongation at 600 lbf | 1.6%

Elongation at 1000 lbf | 2.2%

Elongation at 10% MBS | 1.4–2.2%

Compliant | NFPA 1983 (2012), G

Tags

[made in USA](#), [Rope Rescue](#), [Confined Space](#), [Rope Access](#), [Tower Work](#), [Fire Rescue](#), [Wilderness Rescue](#), [Ropes Course](#), [Cave Rescue](#), [Recreational Caving](#), [Utilities Safety](#), [Industrial Rescue](#)

Product Code

PR130BG092PP | Blue/White/Green | 92 m (300 ft)

PR130BG046PP | Blue/White/Green | 46 m (150 ft)

PR130BG030PP | Blue/White/Green | 30 m (100 ft)

PR130BG183PP | Blue/White/Green | 183 m (600 ft)

PR130cc000PP | Orange/White/Green | 46 m (150 ft)

PR130OG030PP | Orange/White/Green | 30 m (100 ft)

PR130OG092PP | Orange/White/Green | 92 m (300 ft)

PR130OG183PP | Orange/White/Green | 183 m (600 ft)

PR130BG061PP | Blue/White/Green | 61 m (200 ft)

PR130BG200PP | Blue/White/Green | 200 m (656 ft)

PR130OG061PP | Orange/White/Green | 61 m (200 ft)

PR130OG200PP | Orange/White/Green | 200 m (656 ft)

