



TECHNICAL SHEET

1st MOTOR BRAND, MODEL, ORIGIN	DEWERT / MEGAMAT2 / 2000 N / IPX6 / DC or LINAK / LA27 / 3500 N / IPX4 / DC
2nd MOTOR BRAND, MODEL, ORIGIN	DEWERT / MEGAMAT2 / 4000 N / IPX6 / DC or LINAK / LA27 / 6000 N / IPX4 / DC
3rd MOTOR BRAND, MODEL, ORIGIN	DEWERT / GAMMA COLUMN / 2000 N / IPX6 / COLUMN or LINAK / BL1 / 2000 N / IPX4 / COLUMN
4th MOTOR BRAND, MODEL, ORIGIN	DEWERT / GAMMA COLUMN / 2000 N / IPX6 / COLUMN or LINAK / BL1 / 2000 N / IPX4 / COLUMN
COLUMN SYSTEM	2 COLUMN, LINAK or DEWERT BRAND
OXYGEN TUBE HOLDER	OXYGEN TUBE HOLDER ON BOTTOM FRAME OF STRETCHER
GENERAL SIZES (BUMPER TO BUMPER)	WIDTH : 990 mm, LENGHT : 2140 mm
HEIGHT MIN / MAX	520 mm / 920 mm
MOVEMENTS BY MOTORS	BACKREST, LEGREST, HEIGHT, TRENDELENBURG, REVERSE TRENDELENBURG MOVEMENTS
CONTROL PANELS	PATIENT REMOTE CONTROLLER
TRENDELENBURG / REVERSE TRENDELENBURG	TRENDELENBURG : 17° / REVERSE TRENDELENBURG : 17°
BED SURFACES	FULL HPL (8 MM COMPACT) for X-RAY
METAL STRUCTURE	THICKNESS FOR BOX PROFILE : 1,2 - 3,00 mm, FOR PIPE 1,2 - 2,00 mm.
X-RAY	YES. FULL X-RAY SYSTEM FROM HEAD to FOOT
X-RAY CASSETTE HOLDER	YES. FULL BED SURFACES
CASTORS	DIAMETER 200 mm / TENTE or HAION. 4 PIECES.
5th CASTOR	125 mm
PROTECTION BUMPERS	4 PCS BUMPERS ON CORNERS, DIAMETER : 125 mm
BATTERY	YES - STANDART
GUARANTEE	2 YEARS GENERAL + 5 YEARS for MOTORS
DRAINAGE HOOKS & URINE BAG HOLDER	2 PCS
MANUAL KNEE MECHANISM	KNEE MECHANISM with RATCHET MECHANISM
MAX.SAFE CAPACITY	290 KG
COATING TYPE	NANO TECHNOLOGY ELECTROSTATIC POWDER COATING AND COATING THICKNESS MIN : 40 - 90 µm.
MANUAL CPR	MANUAL CPR CAN BE CONTROLLED WITH THE HELP OF HANDLES ON THE RIGHT AND LEFT SIDES.
SIDE RAILS (2 PCS) STRUCTURE	PRODUCED FROM CHROM / CHROMED.METAL AND ALUMINIUM MATERIAL, LOCKABLE SIDE RAILS. FOR SAFE USE OF THE STRETCHER, THE STRETCHER HAS HORIZONTALLY FOLDING SIDE SAILS PROTECTORS. THE UPPER PART OF THE SIDE RAILS ARE MADE OF ALUMINIUM, THE INTERCONNECTION POINTS (5 Pcs - 19 mm) ARE MADE OF STAINLESS STEAL MATERIAL AND THE JOINTS ARE MADE OF PLASTIC MATERIAL.
INFUSION POLE	STAINLESS STEEL, WALL THICKNESS 1,5 mm + PIPE OUTSIDE DIAMETER 25 mm, INNER DIAMETER 19 MM, with 2 PLASTIC HOOKS
MATTRESS	700 x 1980 x 80 mm, 32 DENSITY, WATER RESISTANT, FIRE RETARDANT MATTRESS (UPHOLSTERY). THE MATTRESS ON THE STRETCHER IS EASILY REMOVABLE, ERASABLE AND HAS A THICKNESS of APPROXIMATELY 80 mm
LOCKING OF CASTORS	CENTRAL LOCKING SYSTEM, 1.STEP (UP) : DIRECTIONAL CASTOR (YELLOW COLOUR) , 2.STEP (MIDDLE) : FREE CASTORS (FOR ALL CASTORS), 3.STEP (DOWN) : BRAKE OPEN FOR 4 CASTORS. 2 PEDALS + 1 BAR
CERTIFICATES	CE, TSE, TUV, TUV THURINGEN, IQNET, ISO 9001:2008, TS 12559, TS 12487, TS 13005, TS EN ISO 13485, TS EN IEC 17025, ISO 14001, OHSAS 18001CE, FDA, SFDA etc.

